

GBG - 1 SERIES

Gasoline Generators



Features and Benefits

- Half century experience in generator manufacturing
- Gasoline engines with advanced technology and quality
- Alternators with advanced technology and quality
- Easy to Carry
- High quality and reliable technology
- Compact Design and Silent
- Suitable for heavy-duty
- Durable
- Wide range of affordable spare parts
- Low noise level
- Low exhaust emission
- Low operating cost
- Low fuel consumption
- Low oil consumption
- Lightweight
- Big Size Fuel Tank
- First class product support
- Global technical service and maintenance support

CAUTION: Important Notes;

Note 1: Never use the generator indoors

Note 2: Wait at least 20 minutes for generator to cool off before refuel

Note 3: Do not refuel while the generator is still running

Note 4: Do not use the generator for longer than the continuous operating hours written on the catalog

Factory Address

ASO II. Industrial Zone
2010 Street No: 18
06909 Temelli-Sincan/Ankara, Turkey
Tel/ Fax: +90(312) 641 32 22 - 641 32 23
genpower@genpower.com.tr
www.genpower.com.tr



GENPOWER
GENERATOR

GBG 110E

PRODUCT DATASHEET

GENERATOR

Type		Open Type Standard Portable Generators
Max. Output Power	kVA	10,5
Rated Output Power	kVA	9
Power Factor	Cos Q	0,8
Frequency	Hz	50
Voltage	V	230
Current	A	39
Noice Level (from 7 meter @ 1/4 Load)	dB(A)	≤75

GASOLINE ENGINE

Type		OHV, Single Cylinder, Forced Air Cooled, Four Stroke
Model	GBE	190
Series		FB
Displacement	cc	460
Bore x Stroke	mm	92 x 69
Compression Ratio		8.5:1
Ignition		TCl - Transistor Electronic Ignition
Fuel Tank Capacity	Lt	27
Run Time @ %50 Load	Hour	6
Fuel Consumption	Lt/h	0,374 gr/kWh - 2,69 Lt/h with Full Load
Oil Capacity	Lt	1,1
Engine Start System		Electric Start/Recoil
Speed	rpm	3000

ALTERNATOR

Model		150L
Type		Self Excited, Synchron Alternator
Phase		Single Phase
Voltage Regulation		AVR
Protection Class		IP23
Insulation Class		H/F
Wire	100%	Copper
THD (Total Harmonic Distorsion)	%	≤10-15

OTHER DATA

Over Load Protection		√
Low Oil Alert		√
Reset Socket		√
European Socket		√
Analog Voltmeter		√
3-in-1 director light(oil, output, overload alert)		-
Engine Switch		√
3 in 1 Digital Display		-
DC Socket (12V/8,3A)		√
DC Protector		√
USB Socket		-
Parallel Socket		-
Grounding Terminal		√
Wheel and Handle		√
Certification		CE/EUS/EPA

DIMENSIONS

Package		Carton
Carton Size	cm	70x53x56
Net Weight/Gross Weight	Kg	83/84
Container Loading Qty's 20GP/40GP/40HQ	Pcs	140/288/294

GENPOWER
GENERATOR